

TECHNICAL DATA SHEET

en

Name of product:

FAXE Hard Wax Oil Industry 0249

Type of product: Wood Oil based on refined vegetable oils, resin and wax.

Application: Oil treatment of wooden floors. Can be used for all wood types.

Properties: FAXE Hard Wax Oil Industry leaves an extreme durable surface, with the depth of the oil and the repellent wax content.

Solids: 65 weight % 62 vol. %

Pre-treatment: The wood has to be sanded, clean and dry. If needed a treatment with Faxe Special Lye, series 0288 can be done. Special Lye stops the yellowing of the wood.

Application:

Method:

Industrial roller coater

Recommended viscosity:

No thinning required

Thinner:

Drying:

	Drying time	Film thickness - dry
Dry to use	4 hours 20 °C	9 - 12 g / m ²

System Specification:

If necessary 1x FAXE Industrial Lye
If necessary 1x sanding
1x FAXE Hard Wax Oil Industry

Coverage: Theoretical: 51 m²/ltr.

Storage: Store at 5-20°C

Shelf-life: 24 Months in an unopened container

Note: Faxe Hard Wax Oil Industry provides a repellent effect against waste of example coffee and red wine.

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

EFApaint A/S, Energivej 13, DK-6700 Esbjerg

TLF. +45 75 12 86 00 e-mail: info@efapaint.dk

www.efapaint.dk